

PR3000

The PR3000 Park and Ride validator is designed specifically for the use in private parking systems, with potential integration into public transport projects.

The PR3000 supports all major smart cards compliant to ISO 14443 Type A and B standards, Felica, and Vicinity (13.56 MHz).

The powerful microprocessor ensures a high-speed transaction processing.

The PR3000 is equipped with the EMV3000 contactless card reader, which is EMV L1 certified, EMV L2 certified for Mastercard, Visa, American Express, Discover and Pure, and PCI PTS POI 5.1 certified.

Two on-board SAM card slots and one reader SAM card slot for holding payment SAM cards ensure the security and integrity of the transactions.

For user ergonomics, the PR3000 is equipped with a high-resolution graphic TFT display and a 3" receipt printer.



Key features

- Support for Linux operating system
- 2 On-board SAM card slots, 1 reader SAM card slot
- 3.5" 320x240 graphic TFT display
- I2S Audio codec
- 3" Receipt printer
- I/O interfaces for controlling loops and beams
- EMV3000 contactless card reader
- Compact dimensions to ease installation

Options

- Barcode reader
- VOIP module
- 4G/LTE modem
- WIFI
- Bluetooth

Mechanical

Dimensions	Millimetres	Inches
Enclosure (without solar cover):	1160 H x 324 W x 316 D	45.66 H x 12.76 W x 12.44 D
Weight	Grams	Lbs
Enclosure (depending options):	3500	77.16

Environmental

Temperature	Celsius	Fahrenheit
Operating temperature:	-20 °C to +70 °C	-4 °F to +158 °F
Storage temperature:	-30 °C to +80 °C	-22 °F to +176 °F
Humidity		
Operating humidity:	< 75% RH	
Storage humidity:	< 93% RH	

Electronic

Intelligence:	Single core ARM Cortex A7 CPU Option: Up to quad core A53 CPU
Memory:	512MB/2GB DDR3 memory 4GB-32GB eMMC
Storage:	Option: microSD flash drive
Interface types:	1 Ethernet 10/100/1000 Mbit 1 RS232 8 Digital inputs/outputs
Display:	3.5" Colour graphic TFT display 320x240 pixels Light sensor for automatic backlight adaptation
Keyboard:	Multitouch capacitive touchscreen
Audio:	PWM audio On-board I2S codec with internal speaker Option: VOIP module
Card reader:	EMV3000 contactless smart card reader, EMV L1 certified, EMV L2 certified for Mastercard, Visa, American Express, Discover and Pure, and PCI PTS POI 5.1 certified Option: Other EMV payment kernels (JCB, CUP ...) Option: Barcode reader
Security:	2 On-board SAM card slots, 1 SAM card slot in EMV3000
Communications:	Options: 4G/LTE modem, WIFI, Bluetooth
Printer:	3" Receipt printer
Power supply:	230V AC Internal heating and ventilation