

## MG3000-ABT

The MG3000-ABT gate based ticketing validator is designed specifically for the integration in barriers or turnstiles used in Automatic Fare Collection (AFC) systems for closed public transport areas, e.g. metro, ferries, trams, railway.

The MG3000-ABT supports all major smart cards compliant to ISO 14443 Type A and B standards, Felica, and Vicinity (13.56MHz).

The powerful microprocessor ensures a high-speed transaction processing.

The MG3000-ABT is equipped with the EMV3000 contactless card reader, which is EMV L1 certified, EMV L2 certified for Mastercard, Visa, American Express, Discover and Pure, and PCI PTS POI 5.1 certified.

Two on-board SAM card slots and one reader SAM card slot for holding payment SAM cards ensure the security and integrity of the transactions.

For user ergonomics, the MG3000-ABT is equipped with a high-resolution graphic TFT display.



### Key features

- Support for Linux operating system
- 2 On-board SAM card slots, 1 reader SAM slot
- 3.5" 320x240 Graphic TFT display
- I2S Audio codec
- EMV3000 contactless card reader
- Compact dimensions to ease installation

### Options

- Barcode reader
- 4G/LTE modem



## Environmental

Temperature	Celsius	Fahrenheit
Operating temperature:	-20 °C to +70 °C	-4 °F to +158 °F
Storage temperature:	-30 °C to +80 °C	-22 °F to +176 °F
<b>Humidity</b>		
Operating humidity:	< 75% RH	
Storage humidity:	< 93% RH	

## Electronic

Intelligence:	Single core ARM Cortex A7 CPU Option: Up to quad core A53 CPU
Memory:	512MB/2GB DDR3 memory 4GB-32GB eMMC
Storage:	Option: microSD flash drive
Interface types:	1 Ethernet 10/100/1000 Mbit
Display:	3.5" Colour graphic TFT display 320x240 pixels Light sensor for automatic backlight adaptation
Audio:	PWM audio On-board I2S codec with internal speaker
Card reader:	EMV3000 contactless smart card reader, EMV L1 certified, EMV L2 certified for Mastercard, Visa, American Express, Discover and Pure, and PCT PTS POI 5.1 certified Option: Other EMV payment kernels (JCB, CUP ...) Option: Barcode reader
Security:	2 On-board SAM card slots, 1 SAM card slot in EMV3000
Communications:	Option: 4G/LTE modem
Power supply:	Switched mode power supply Wide input voltage (10-36V) Option: PoE